



Product Service

Attestation of Conformity

No. N8A 16 12 96291 003

Holder of Certificate: Top Win Optoelectronics Corp.5F.-2, No. 120, Qiaoh Rd.
Zhonghe Dist.
23584 New Taipei City
TAIWAN**Product: Luminaires for road and street lighting
(LED Street Light)****Model(s):** TW-PD0365011-D5, TW-PD0555011-D5,
TW-PD0725011-D5, TW-PD0855011-D5,
TW-PD0905011-D5, TW-PD1105011-D5,
TW-PD1355011-D5**Parameters:**
Rated voltage: 100-240 Vac
Rated frequency: 50/60 Hz
Rated current: See attachment
Rated power: See attachment
Protection class: I
IP class: IP65
ta: 60 °C**Tested according to:** EN 60598-2-3:2003/A1:2011
EN 60598-1:2015
EN 62471:2008
EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 611401607001
(Bill Lin)**Date,** 2016-12-20**CE** After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 2



1. Trade mark:



2. The rated input and differences of models are as below:

Model-#	Rated input voltage (Vac)	Rated input current (A)	Rated input power (W)	Number of LED modules	Dimension (mm)
TW-PD0365011-D5	100-240	0.15-0.36	36	1	150*420*130
TW-PD0555011-D5	100-240	0.23-0.55	55	1	150*420*130
TW-PD0725011-D5	100-240	0.30-0.72	72	2	310*420*130
TW-PD0855011-D5	100-240	0.35-0.85	85	2	310*420*130
TW-PD0905011-D5	100-240	0.38-0.90	90	2	310*420*130
TW-PD1105011-D5	100-240	0.46-1.10	110	2	310*420*130
TW-PD1355011-D5	100-240	0.56-1.35	135	3	470*420*130

Date, 2016-12-20