


TEST REPORT IEC 62722-2-1: 2014 LUMINAIRE PERFORMANCE – Part 2-1: Particular requirements for LED luminaires	
Report No.	OI-2016-B0167
Date of issue	Dec. 28, 2016
Testing Laboratory	SGS Taiwan Ltd., Optics Laboratory
Address	No. 33, Wu Chyuan Road, New Taipei Industrial Park, Wu Ku District, New Taipei City 24886, Taiwan (R.O.C.)
Applicant's name	Top Win Optoelectronics Corp.
Address	5F. -2, No. 120, Qiaohe Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)
Test specification:	
Standard	IEC 62722-2-1: 2014 LUMINAIRE PERFORMANCE – Part 2-1: Particular requirements for LED luminaires
Test procedure	CE Marking Testing
Non-standard test method	N/A
Test item description	55W LED Street Light
Trade Mark	SLITE
Manufacturer	Top Win Optoelectronics Corp.
Model/Type reference	TW-PD0555011-D5
Ratings	AC 100 V to 240 V (50 / 60) Hz, 55 W
Conclusion:	In the opinion of SGS, the submitted <u>Device Under Test</u> (DUT) <u>complies</u> with the IEC 62722-2-1 test specification.
<div style="text-align: right;"> Approved by: Benson DENG Supervisor Dec. 28, 2016 </div>	
<div style="text-align: right;">  _____ Signature </div>	
<p>Details and test results are given in subsequent pages of this report. This report refers only to the unit(s) submitted for test. "(see Enclosure #)" refers to additional information appended to the report. "(see appended table)" refers to a table appended to the report. Throughout this report a point is used as the decimal separator. This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/terms_e-document.htm Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.</p>	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

<input checked="" type="checkbox"/> Testing Laboratory:		SGS Taiwan Ltd., Optics Laboratory		
Testing Location / Address.....:		<input checked="" type="checkbox"/> No. 33, Wu Chyuan Road, New Taipei Industrial Park, Wu Ku District, New Taipei City 24886, Taiwan (R.O.C.) <input type="checkbox"/> No. 61, Kai-Fa Road, Nanzih Export Processing Zone, Kaohsiung 81170, Taiwan (R.O.C.)		
Main Test Equipment:				
Name	Brand	Model	S/N	Calibration Due Date
Digital Power Meter / AC Source	YOKOGAWA / apc	WT-310 / AFC-500W	C2PK22023V/ F312120079	2017/8/18
Goniophotometer	SGS Define (CZIBULA & GRUNDMANN GMBH / everfine)	EVERFINE GO-R5000-PLUS	1001001	2017/2/1
Summary of testing:				
This test report was issued for Energy Efficiency requirements of IEC 62722-2-1 LUMINAIRE PERFORMANCE – Part 2-1: Particular requirements for LED luminaires only. The compliance with the requirements of other applicable standards may be needed in additional test reports.				
Copy of marking plate:				
Please see IV Product Specification. Note: The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

TEST REPORT	
Test item particulars:	
Classification of installation and use	Type I Roadway Lighting
Supply Connection.....	MEAN WELL / HLG-80H-42A
Class of equipment.....	IP65
Mass of the equipment	4.2 kg
Possible test case verdicts:	
– test case does not apply to the test object.....: N (Not applicable)	
– test object does meet the requirement	
– test object does not meet the requirement.....: F (Fail)	
Testing:	
Date of receipt of test item	Nov. 23, 2016
Date (s) of performance of tests	Nov. 23, 2016 ~ Dec. 23, 2016
General remarks:	
<p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p> <p>"(see Enclosure #)" refers to additional information appended to the report.</p> <p>"(see appended table)" refers to a table appended to the report.</p> <p>Clause numbers between brackets refer to clauses in IEC 62722-2-1</p> <p>Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.</p>	
General product information:	
<p>The model No. TW-PD0555011-D5 of 55 W LED Street Light were type I of IEC 60598-1 use for roadway lighting, the IEC 62717 report of LED module No. MD5T01 has been proven for the IEC 62722-2-1 testing.</p> <p>The LED luminaire classification of IEC 62722-2-1 was type A.</p> <p>Note: The test samples were LED module and controlgear combination, the real sample has long arm mounted type fixture kit, but does not affect the testing and requirements.</p>	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

I. Product Specification

LED Luminaire Specification		
Scope Type	:	Type A
Model Name	:	55W LED Street Light
Rated Luminous Flux (lm)	:	6700 lm
Photometric Code	:	750/7 ⁺ 7 ⁺ 9
Rated Life Time (h) and Rated median useful life and the associated rated lumen maintenance factor (x)	:	30000 h / L ₇₀ F ₁₀
Rated Abrupt Failure Value AFV (%)	:	10 %
Lumen Maintenance Code	:	9
Categories of rated chromaticity coordinate values both initial and maintained	:	F5000 (7 ⁺ , 7 ⁺)
Correlated Colour Temperature (K)	:	5000 K
Rated Colour Rendering Index	:	70
<i>t_{q rated}</i> of LED Luminaire (°C)	:	50 °C
Ageing time	:	--
Ambient temperature range (°C)	:	-30 °C to 50 °C
Rated Input Voltage (V)	:	100 to 240 V
Rated Input Current (A)	:	0.23 to 0.55 A
Rated Input Frequency (Hz)	:	(50 / 60) Hz
Rated Input Power (W)	:	55 W
Rated Efficacy (lm/W)	:	122 lm/W
Dimension (mm)	:	W 150 x L 420 x H 130
LED Light Source Specification		
LED Model	:	XPG2
Manufacture / Brand	:	CREE
Rated Input Voltage (V)	:	3.05 V
Rated Input Current (A)	:	750 mA
Rated Input Frequency (Hz)	:	DC
LED Quantity per Module	:	24 pcs
Dimension (mm)	:	W 3.45 x L 3.45 x H 2.26
Controlgear Specification		
Model	:	HLG-80H-42A
Manufacture / Brand	:	MEAN WELL
Rated Input Voltage (V)	:	AC 100 V to 240 V
Rated Input Current (A)	:	0.85 A
Rated Input Frequency (Hz)	:	(50 / 60) Hz
Used Quantity per Luminaire	:	1 pce

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

1	Scope		
	Type A — Luminaires using LED modules where compliance with IEC 62717 has been proven.	IEC 62717 Report No.: OI-2016-70067	P
	Type B — Luminaires using LED modules where compliance with IEC 62717 has not been proven.		N
	Type C — Luminaires using a LED lamp and covered in IEC 62722-1. The standard does not cover Type C luminaires.		N

4	Product information		
	Information as below shall be provided by the manufacturer or responsible vendor on the product datasheets, leaflets or website. Compliance is checked by inspection.	See IV Product Specification	P
	a) Rated input power (in W)	See IV Product Specification	P
	b) Photometric code	See IV Product Specification	P
	c) Rated luminous flux (in lm)	See IV Product Specification	P
	d) Rated median useful life (h) and the associated rated lumen maintenance factor (x)	See IV Product Specification	P
	e) Rated abrupt failure value (%)	See IV Product Specification	P
	f) Lumen maintenance code	See IV Product Specification	P
	g) Rated chromaticity co-ordinate values both initial and maintained	See IV Product Specification	P
	h) Rated correlated colour temperature (CCT in K)	See IV Product Specification	P
	i) Rated colour rendering index (CRI)	See IV Product Specification	P
	j) Rated ambient temperature (t_a) related to performance for a luminaire (°C)	See IV Product Specification	P
	k) Rated LED luminaire luminous efficacy (in lm/W)	See IV Product Specification	P
	l) Ageing time, if different from 0 h	--	N

6	Test conditions		
6.1	General test conditions		--
	All tests are measured on "n" LED luminaires of the same type. The number "n" shall be a minimum of products as given in Table 3.	LED modules where compliance with IEC 62717 has been proven	P
	LED luminaires used in the endurance tests shall not be used in other tests.		P
	Each sample luminaire shall comply with all the relevant tests except for the tests of 10.3 where one sample is required for each of the three separate tests mentioned in Table 2 and Table 3. In order to reduce the time of testing, the manufacturer or responsible vendor may submit additional luminaires or parts of luminaires provided that these are of the		P

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	same materials and design as the original luminaire and that the results of the test are the same as if carried out on an identical luminaire.		
	LED luminaires with dimming control shall be adjusted to maximum output for all tests.		P
	LED luminaires with adjustable CCT shall be adjusted/set to one fixed value as indicated by the manufacturer or responsible vendor.	Not an adjustable CCT luminaire	N
	LED luminaires of linear geometry and variable length shall be tested at a length at which the parameters are given (e.g. performance per x cm).	Not linear geometry and variable length product	N
6.2	Luminaires using LED modules where compliance with IEC 62717 has been proven (Type A)		--
	Only the tests for measurement of initial performance are to be conducted, when the LED module is operated within its temperature limit t_p .		P
	The information for luminaire design given in IEC 62717, Clause B.1, requires LED modules to be operated within their t_p temperature limit. The t_p temperature shall be measured according to the thermal test procedure defined in 12.4 of IEC 60598-1, (normal operation). When the luminaire is operating at its own maximum rated ambient temperature for performance (t_q), the t_p limit (for the declared performance — Table 2, IEC 62717) of LED modules operating inside the luminaire shall not be exceeded. The test voltage for the luminaire shall be 1.00 times the rated voltage of the luminaire. In luminaires intended to be supplied with constant current, the test current shall be 1.00 times the rated current of the luminaire.		P
	For luminaires for road and street lighting and floodlights intended for outdoor use only, the reduction of the measured temperature according to 3.12.1 of IEC 60598-2-3, and 5.12.1 of IEC 60598-2-5, respectively shall not be applied for the t_p temperature of the LED module.		P
	The ambient performance temperature t_q is measured in a draught-proof enclosure, as the air temperature, at a position near one of the perforated walls on a level with the centre of the luminaire, see item e), Clause K.1 of IEC 60598-1.		P
6.3	Luminaires using LED modules where compliance with IEC 62717 has not been proven (Type B)		N
6.3.1	General		
	The manufacturer shall conduct testing for 25 % of rated life up to a maximum of 6 000 h.		N

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.3.2	Creation of module families to reduce test effort		--
6.3.2.1	General		N
	The provisions of 6.2.1 of IEC 62717 apply to the LED luminaire.		
6.3.2.2	Variations within family		N
	The provisions of 6.2.2 of IEC 62717 apply to the LED luminaire.		
6.3.2.3	Compliance testing of family members		N
	The provisions of 6.2.3 of IEC 62717 apply to the LED luminaire.		
6.4	Performance requirements		P
	The performance criteria given in Table 2 applies for LED luminaires of Types A and B. All of the tested n LED luminaires shall have passed the performance requirements.	Luminaire of type A	
7	Input power		
	Power shall be measured at the supply to the luminaire, see Figure 1. The provisions of Clause 7 of IEC 62717 apply to the LED luminaire. In case the power is not constant, the average of the power is measured over an appropriate time.	See II. TESTING VALUE	P
8	Photometric performance		
8.1	Luminous flux		--
	Measured luminous flux (lm)		P
	The initial luminous flux of each individual LED luminaire in the measured sample shall not be less than the rated luminous flux by more than 10 %.	See II. TESTING VALUE	P
8.2	Luminous intensity distribution, peak intensity and beam angle.		--
8.2.1	General		
	The requirements of 8.2.4 and 8.2.5 shall be applied to LED luminaire having a directional (spot) distribution.	See II. TESTING VALUE	P
8.2.2	Measurement		
	The intensity of light emitted from the LED luminaire in different directions is measured using a goniophotometer. All photometric data shall be declared for the LED module operating at its temperature $t_{p rated}$ per Clause A.1. The allowed photometric variations detailed should take account of manufacturing tolerances.	See II. TESTING VALUE	P
8.2.3	Luminous intensity distribution		--
	The distribution of luminous intensity shall be in accordance with that declared by the manufacturer.	See II. TESTING VALUE	P

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	The measurement is conducted according to A.3.3.		
	Compliance is under consideration.	Under consideration	N
8.2.4	Peak intensity	See II. TESTING VALUE	P
	The initial peak intensity of a LED luminaire shall not be less than 75 % of the rated intensity.		
8.2.5	Beam angle	See II. TESTING VALUE	P
	The beam angle value of a LED luminaire shall not deviate by more than 25 % of the rated value.		
8.3	Luminaire luminous efficacy		--
	Measured efficacy (lm/W)	See II. TESTING VALUE	P
	The efficacy of LED luminaire shall not be less than 90% of the rated efficacy	See II. TESTING VALUE	P

9	Chromaticity co-ordinates, correlated colour temperature (CCT) and colour rendering		
9.1	Chromaticity co-ordinates		--
	Measured initial / maintained chromaticity co-ordinates	See II.F to I of IEC 62717 report : OI-2016-70067	P
	The measured chromaticity co-ordinate values of a LED module (the initial value and maintained value) shall not move beyond the chromaticity co-ordinate tolerance category	See II.G of IEC 62717 report : OI-2016-70067	P
9.2	Correlated colour temperature (CCT)		--
	Measured initial / maintained CCT.	See II.F to I of IEC 62717 report : OI-2016-70067	P
	The measured correlated colour temperature shall not move beyond the value as declared.	Rated value: 5000 K	P
9.3	Colour rendering index (CRI)		--
	Measured initial / maintained CRI.	See II.F to I of IEC 62717 report : OI-2016-70067	P
	For all tested item in the sample the measured CRI values shall not have decreased by more than:	Rated value: 70	--
	- 3 points from the rated CRI value (see Table 1) for initial CRI values;	See II.F to I of IEC 62717 report : OI-2016-70067	P
	- 4 points from the rated CRI value, when tested for 6 000 h maintained CRI values.	See II.F to I of IEC 62717 report : OI-2016-70067	P

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

10	LED luminaire life		
10.1	General		N
10.2	Lumen maintenance		N
	Measured maintained luminous flux		N
	The measured luminous flux value shall not be less than the luminous flux value given by the rated lumen maintenance factor related to rated median useful life.	Luminaire of type A (LED modules compliance with IEC 62717)	N
	For all the tested items in a sample, the measured values shall be of the same maintenance code as the provided values. All the LED modules in a sample shall pass the test.	Luminaire of type A (LED modules compliance with IEC 62717)	N
10.3	Endurance tests	Luminaire of type A (LED modules compliance with IEC 62717)	N
(10.3.1) (IEC 62717)	General		N
(10.3.2) (IEC 62717)	Temperature cycling test		N
(10.3.2.1) (IEC 62717)	General		N
(10.3.2.2) (IEC 62717)	Alternative test 1 with 10 K/min		--
	At the end of the test all the LED luminaire shall operate and have a luminous flux which stays within the claimed lumen maintenance code for a period of at least 15 mm and show no physical effects of temperature cycling such as cracks or delaminating of the label.	Luminaire of type A (LED modules compliance with IEC 62717)	N
(10.3.2.3) (IEC 62717)	Alternative test 2 with 1 K/min		--
	At the end of the test all the LED luminaire shall operate and have a luminous flux which stays within the claimed lumen maintenance code for a period of at least 15 mm and show no physical effects of temperature cycling such as cracks or delaminating of the label.	Luminaire of type A (LED modules compliance with IEC 62717)	N
(10.3.3) (IEC 62717)	Supply switching test		--
	At test voltage, current or power, the LED luminaire shall be switched on and off for 30 s each. The cycling shall be repeated for a number equal to half the rated life in h.	Luminaire of type A (LED modules compliance with IEC 62717)	N
	At the end of the test all the LED luminaire shall operate and have a luminous flux which stays the claimed lumen maintenance code for a period of at least 15 mm.	Luminaire of type A (LED modules compliance with IEC 62717)	N

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IEC 62722-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
(10.3.4) (IEC 62717)	Accelerated operation life test		--
	The LED luminaire shall be operated continuously without switching at test voltage and at a temperature corresponding to 10 K (see last paragraph) above the maximum recommended operating temperature $t_{p, rated}$, over an operational time of 1 000 h. Any thermal protecting devices that would switch off the LED luminaire or reduces the light output at a threshold temperature $> t_{p, rated}$ shall be bypassed.	Luminaire of type A (LED modules compliance with IEC 62717)	N
	At the end of this period, and after cooling down to room temperature and being stabilised, all the LED luminaire have an allowed decrease of light output at the end of the test of max. 20 % compared to the initial value, for at least 15 min.	Luminaire of type A (LED modules compliance with IEC 62717)	N

11	Verification		
	Sample sizes and DUT S/N	See table below	P

Clause	Test	Type and S/N
6.3	LED module performance temperature	A1
7	Power	
8.1	Luminous flux	
8.2.3	Luminous intensity distribution	
8.2.4	Intensity value	
8.2.5	Beam angle value	--
8.3	Luminaire luminous efficacy	
9.1	Initial chromaticity tolerance	
9.1	Maintained chromaticity tolerance	
9.2	Initial correlated colour temperature	
9.3	CRI initial	
9.3	CRI maintained	
10.2	Lumen maintenance	
10.3(10.3.2)	Temperature cycling, energised	--
10.3(10.3.3)	Supply voltage switching	--
10.3(10.3.4)	Accelerated operation life test	--

Note: The test samples were without erect poles.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


II. TESTING VALUE

A. LED Luminaire performance temperature


S/N	Input Voltage	Input Current	Input Power	t_g Temp.(°C)
A1	219.98	0.2614	56.06	44.0

B. Luminous intensity distribution

S/N A1



Polar Luminous Intensity Distribution



Cartesian Coordinates Luminous Intensity Distribution

C. Peak intensity & Beam angle

S/N	Peak intensity (cd)	Beam angle (50%)(°)
A1	7115.01 cd	100.3°

D. Optical Properties & Electrical Characteristics

Initial (0 h)								
S/N	Input Voltage	Input Current	Input Power	Luminous Flux	CCT	CRI(Ra)	SDCM	Luminous Efficacy
A1	219.99	0.2630	56.23	6738.5	4918	71.6	1.68	119.8


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

III. Attachment Photos



Front View



Back View

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



DUT



Control Gear





Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IV. Product Specification


德威光電股份有限公司 Top Win Optoelectronics Corp.

Street Light - SLITE Series	File Number :	Edition : A0
	Formulate : Product Integration Dept.	Pages : 1/7

	Height of poles (H)	Applicable luminaire
	< 8M	36W~55W SLITE 
	8~12M	72W~110W SLITE 
	> 12M	135W SLITE 

Note: The Figure above is for reference only. To achieve the best result, it should simulate each road conditions.

PHOTOMETRY



表單編號: QP-702-14 版次: A0

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

德威光電股份有限公司
Top Win Optoelectronics Corp.

Street Light - SLITE Series

File Number :


Edition : A0

Formulate : Product Integration Dept.

Pages : 2/7

Specification

1 Module



36W~55W

2 Module



72W~110W

3 Module



135W

Model number	Luminaire Wattage (W)	Luminous Flux (lm)	Luminaire Efficacy (lm/W)	Weight (kg)	Dimensions (cm)	EPA (cm ²)
TW-PD0365011-D5	36	4600	128	< 4.2	15*42*13	594
TW-PD0555011-D5	55	6700	122	< 4.2	15*42*13	594
TW-PD0725011-D5	72	9200	128	< 6.6	31*43*13	1150
TW-PD0855011-D5	85	10700	126	< 6.6	31*43*13	1150
TW-PD0905011-D5	90	11250	125	< 6.6	31*43*13	1150
TW-PD1105011-D5	110	13400	122	< 6.6	31*43*13	1150
TW-PD1355011-D5	135	16850	125	< 8.9	47*43*13	1687

Input Voltage	100~240VAC
Frequency	50/60Hz
Operating Temperature	-30°C ~ 50°C
Color Temperature	5000 K
CRI	Ra ≥ 70
Photometric Code	750/7'7'9
Categories of rated chromaticity coordinate values	F5000 (7', 7')
Lumen Maintenance Code	9
Case Material	AL 6063 T6
Ingress Protection	IP65
Certification	CE
Life	≥ 30,000 hrs (L70F10)

表單編號: QP-702-14 版次: A0

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

德威光電股份有限公司
Top Win Optoelectronics Corp.

Street Light - SLITE Series

File Number :

Edition : A0

Formulate : Product Integration Dept.

Pages : 3/7

Simulation for roadway lighting :


36~55W Street Light: (This is for reference, the simulation of actual roadway is principal.)

Street Profile

Roadway 1 (Width: 15.000 m, Number of lanes: 4, tarmac: R3, q0: 0.070)

Light loss factor: 0.80

Luminaire Arrangements



Luminaire	TW-PD0365011-D5	TW-PD0555011-D5
Luminous flux(Luminaire)	4600 lm	6700 lm
Luminaire Wattage	36 W	55 W
Arrangement	Double row, opposing	
Pole Distance	20 M	
Mounting Height	7 M	
Height	7 M	
Overhang	0.5 M	
Boom Angle	15°	
Boom Length	1 M	
E_{av} [lx]	19	27
E_{min} [lx]	12	18
E_{max} [lx]	23	34
$u0$	0.669	0.669
E_{min} / E_{max}	0.534	0.534

表單編號: QP-702-14 版次: A0

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

德威光電股份有限公司
Top Win Optoelectronics Corp.

Street Light - SLITE Series

File Number :

Edition : A0

Formulate : Product Integration Dept.

Pages : 4/7


72~110W Street Light: (This is for reference, the simulation of actual roadway is principal.)

Street Profile

Roadway 2 (Width: 7.500 m, Number of lanes: 2, tarmac: R3, q0: 0.070)
Median 1 (Width: 1.000 m, Height: 0.000 m)
Roadway 1 (Width: 7.500 m, Number of lanes: 2, tarmac: R3, q0: 0.070)

Light loss factor: 0.80

Luminaire Arrangements



Luminaire	TW-PD0725011-D5	TW-PD0855011-D5	TW-PD0905011-D5	TW-PD1105011-D5
Luminous flux(Luminaire)	9200 lm	10700 lm	11250 lm	13400 lm
Luminaire Wattage	72 W	85 W	90 W	110 W
Arrangement	on Median			
Pole Distance	35 M			
Mounting Height	12 M			
Height	12 M			
Overhang	1.5 M			
Boom Angle	15°			
Boom Length	2 M			
Roadway1 E _{av} [lx]	17	20	21	25
Roadway1 E _{min} [lx]	13	15	15	18
Roadway1 E _{max} [lx]	23	26	28	33
Roadway1 u0	0.747			
Roadway1 E _{min} / E _{max}	0.557			
Roadway2 E _{av} [lx]	17	20	21	25
Roadway2 E _{min} [lx]	13	15	15	18
Roadway2 E _{max} [lx]	23	26	28	33
Roadway2 u0	0.747			
Roadway2 E _{min} / E _{max}	0.557			

表單編號: QP-702-14 版次: A0

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

德威光電股份有限公司
Top Win Optoelectronics Corp.

Street Light - SLITE Series

File Number :

Edition : A0

Formulate : Product Integration Dept.

Pages : 5/7


135W Street Light: (This is for reference, the simulation of actual roadway is principal.)

Street Profile

Roadway 2 (Width: 10.500 m, Number of lanes: 3, tarmac: R3, q0: 0.070)
Median 1 (Width: 1.000 m, Height: 0.000 m)
Roadway 1 (Width: 10.500 m, Number of lanes: 3, tarmac: R3, q0: 0.070)

Light loss factor: 0.80

Luminaire Arrangements



Luminaire	TW-PD1355011-D5
Luminous flux(Luminaire)	16850 lm
Luminaire Wattage	135 W
Arrangement	on Median
Pole Distance	35 M
Mounting Height	12 M
Height	12 M
Overhang	1.5 M
Boom Angle	15°
Boom Length	2 M
Roadway1 E_{av} [lx]	27
Roadway1 E_{min} [lx]	15
Roadway1 E_{max} [lx]	42
Roadway1 $u0$	0.55
Roadway1 E_{min} / E_{max}	0.363
Roadway2 E_{av} [lx]	27
Roadway2 E_{min} [lx]	15
Roadway2 E_{max} [lx]	42
Roadway2 $u0$	0.55
Roadway2 E_{min} / E_{max}	0.363

表單編號: QP-702-14 版次: A0


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

德威光電股份有限公司
Top Win Optoelectronics Corp.

Street Light - SLITE Series	File Number :	Edition : A0
	Formulate : Product Integration Dept.	Pages : 7/7

Warning:

- Operation condition: 100~240 VAC, -30℃~60℃.
- For your safety, please cut off the power before installation.
- Please ensure the installation location can bear more than 10 times weight of the luminaire.
- Put down gently when moving the luminaire.
- Please do not try to disassemble, repair or modify the luminaire or the product is not within the company warranty.
- If there aren't green or green-yellow ground wires on the luminaire, please connect the AC ground wire onto the lamp housing or the pole.
Cautions: For the safety of the lamp, please make sure the grounding must be completed. Any damages caused by without following the installation instruction, the product is not within the company warranty.
- Do not scratch the wires when connecting.
- Installing Surge Protective Device could effectively reduce the risk of damage of LED luminaire from lightning strike. The wiring replacement is according to page 2 if damage caused. (consumables)
- The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer than 0.823m is not expected.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire shall be destroyed.
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.
-  Don't touch the luminaire after powering up to avoid the risk of electric shock.
- The product is not within the scope of the warranty if there's damage caused by natural disasters, floods or earthquake.

表單編號: QP-702-14 版次: A0

- End of Report -

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明，此報告結果僅對測試之樣品負責。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.